

## Coaxial Cable Connector 25\_TNC-50-2-19/133\_N

### Description

Straight panel cable jack, flange mount

Interface standards

IEC 60169-17\_MIL-STD-348A/313\_CECC 22200



### Technical Data

#### Electrical Data

Impedance	50 $\Omega$
Interface frequency max.	11 GHz
Frequency range	DC to 2.5 GHz
Return loss	32 dB

#### Mechanical Data

Centre contact	crimped
Outer contact	crimped
Weight	0.0167 kg

#### Environmental Data

Operating temperature	-65 °C to 165 °C
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant

#### Material Data

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium / Brass	Gold Plating (Nickel underplated)
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Crimp ferrule	Brass	SUCOPLATE (R) Plating

### Related Documents

Outline drawing	DOU-00073555
Assembly instruction	DOC-0000231469

### Ordering Information

Single package	25_TNC-50-2-19/133_NE
----------------	-----------------------

### Additional Information

Suitable cables	RG_316_/U, ENVIROFLEX_316, RG_188_A/U, RG_174_/U
-----------------	--

### Remarks

El. optimized for cable RG\_316\_/U