

**Basic features**

Approval/Conformity	CE UKCA cETLus WEEE
Component	Base
Function	IO-Link signal transmission
Use	for inductive coupler remote BIC007H

**Display/Operation**

Active transmission indicator	yes
Function indicator	yes
Power indicator	yes

**Electrical connection**

Connection	M12x1-Male, 4-pin
Short-circuit protection	yes

**Electrical data**

Rated operating voltage Ue DC	24 V
Signal type	bi-directional
Type of master port	A

**Environmental conditions**

Ambient temperature	-5...55 °C
IP rating	IP67
Interference immunity	EN 61000-4-2/3/4/5/6
Storage temperature	-25...70 °C

**Functional safety**

MTTF (40 °C)	51.1 a
--------------	--------

Inductive Couplers  
**BIC 1B0-IT1A7-Q40KFU-SM4A4A**  
Order Code: BIC007F

**BALLUFF**

**Interface**

Additive cycle time	Device + 2.8 ms
IO-Link version	1.1
Interface	IO-Link 1.1
Process data IN	0...32 bytes
Process data OUT	0...32 bytes
Process data cycle min.	2.8 ms
SIO mode	no
Transfer rate	COM2 (38.4 kBaud) COM3 (230.4 kBaud)

**Material**

Housing material	PBTP
Material sensing surface	PBTP

**Mechanical data**

Dimension	40 x 40 x 62 mm
Frame type	Device dependent
Installation	non-flush
Offset	±5 mm
Tightening torque max.	40 Nm
Tightening torque pigtail	0.6 Nm
Weight	150 g

**Range/Distance**

Range	0...5 mm
Transmission distance	0...5 mm

**Remarks**


For additional information, refer to user's guide.

Order accessories separately.

For more information about MTTF and B10d see MTTF / B10d Certificate

Indication of the MTTF- / B10d value does not represent a binding composition and/or life expectancy assurance; these are simply experiential values with no warranty implications. These declared values also do not extend the expiration period for defect claims or affect it in any way.

**Connector Drawings**



IO-Link

PIN 1: +24V

PIN 2: In-/Output

PIN 3: GND

PIN 4: C/Q, IO-Link DC-Channel