

1) Sensing surface, 2) Housing, 3) Potentiometer, 4) LED function indicator



### Basic features

Approval/Conformity	CE cULus LISTED WEEE
Basic standard	IEC 60947-5-2
Scope of delivery	Screwdriver Short guide
Sensitivity	Switching distance adjustable
Series	G06

### Display/Operation

Function indicator	yes
--------------------	-----

### Electrical connection

Connection	M8x1-Male, 3-pin
Polarity reversal protected	yes
Protection against device mix-ups	yes
Short-circuit protection	yes

### Electrical data

No-load current $I_0$ max. at $U_e$	10 mA
Operating voltage $U_b$	11...30 VDC
Rated insulation voltage $U_i$	75 V DC
Rated operating current $I_e$	50 mA
Rated operating voltage $U_e$ DC	24 V
Ripple max. (% of $U_e$ )	10 %
Switching frequency	100 Hz
Utilization category	DC -13
Voltage drop static max.	2 V

### Environmental conditions

Ambient temperature	-10...70 °C
Contamination scale	1
IP rating	IP65

### Functional safety

MTTF (40 °C)	444 a
--------------	-------

### Interface

Switching output	PNP normally closed (NC)
------------------	--------------------------

### Material

Housing material	1.4301 stainless steel
Material sensing surface	PTFE

### Mechanical data

Dimension	Ø 6.5 x 54 mm
Installation	for flush mounting
Size	D6.5

### Range/Distance


Hysteresis H max. (% of $S_r$ )	15.0 %
Measuring range	0.1...1.5 mm
Rated operating distance $S_n$	1.5 mm
Repeat accuracy max. (% of $S_r$ )	2.0 %
Temperature drift max. (% of $S_r$ )	15 %

**Remarks**

The potentiometer does not have a fixed stop, but can be turned endlessly without destroying anything.  
If no change in the switching signal is detected, the potentiometer should be turned forwards or backwards until a signal change occurs at the output.  
For more information about MTTF and B10d see MTTF / B10d Certificate

Indication of the MTTF- / B10d value does not represent a binding composition and/or life expectancy assurance; these are simply experiential values with no warranty implications. These declared values also do not extend the expiration period for defect claims or affect it in any way.

**Connector Drawings**



**Wiring Diagrams**

