

Thermomagnetic device circuit breaker - TMC 83C 63A



1010291

<https://www.phoenixcontact.com/us/products/1010291>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.

Thermomagnetic device circuit breaker, number of positions: 3, connection method: Screw, cross section: 1 mm²- 35 mm², AWG: 18 - 2, mounting type: DIN rail, Color: gray



Commercial Data

Item number	1010291
Packing unit	1 pc
Note	Made to Order (non-returnable)
Sales Key	C29
Product Key	CLA125
GTIN	4055626484037
Weight per Piece (including packing)	222.222 g
Weight per Piece (excluding packing)	222.222 g
Customs tariff number	85362010
Country of origin	CN

Thermomagnetic device circuit breaker - TMC 83C 63A



1010291

<https://www.phoenixcontact.com/us/products/1010291>

Technical Data

Product properties

Type	DIN rail module, one-piece
Product type	Thermomagnetic device circuit breakers
Number of positions	3
Mechanical service life	20000

Electrical properties

Service life electrical	6000
-------------------------	------

General

Operating voltage	240 V AC (Delta)
Rated current I_N	63 A
Tripping method	TM (thermomagnetic)
Rated short-circuit switching capacity I_{cn}	10 kA (IC)
Fuse	C

Connection data

Tightening torque	... 2 Nm
Conductor cross section solid	1 mm ² ... 35 mm ²
Cross section AWG	18 ... 2 (converted acc. to IEC)
Conductor cross section flexible	1 mm ² ... 35 mm ²
Connection method	Screw
Tightening torque, min	2 Nm
Conductor cross section flexible max.	35 mm ²
Conductor cross section solid max.	35 mm ²

Dimensions

Dimensional drawing	
Width	52.9 mm
Height	116 mm
Depth	65.7 mm

Material specifications

Color	gray
-------	------

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-35 °C ... 70 °C
---------------------------------	------------------

Thermomagnetic device circuit breaker - TMC 83C 63A



1010291

<https://www.phoenixcontact.com/us/products/1010291>

Humidity test	48 h, 95% RH, 40°C (IEC 60068-2-78)
Shock (operation)	30g (11 ms) (IEC 60068-2-11)
Vibration (operation)	±0.38 mm (10-57 Hz), 5g (57...500 Hz) (IEC 60068-2-6, Fc, sine)


Standards and regulations

Standards/specifications	UL 489
Standards/specifications	IEC 60947-2


Mounting

Mounting type	DIN rail
---------------	----------

Drawings



Diagram



1010291

<https://www.phoenixcontact.com/us/products/1010291>

Approvals



UL Listed

Approval ID: FILE E 320373



cUL Listed

Approval ID: FILE E 320373



TÜV Rheinland

Approval ID: R 50531587

cULus Listed

1010291

<https://www.phoenixcontact.com/us/products/1010291>

Classifications

ECLASS

ECLASS-9.0	27141116
ECLASS-10.0.1	27141116
ECLASS-11.0	27141116

ETIM

ETIM 7.0	EC000899
----------	----------

UNSPSC

UNSPSC 21.0	39121410
-------------	----------

Thermomagnetic device circuit breaker - TMC 83C 63A



1010291

<https://www.phoenixcontact.com/us/products/1010291>

Accessories

Wiring bridge

Wiring bridge - TMC 8 B3 80 57 C - 2907996

<https://www.phoenixcontact.com/us/products/2907996>




Bus bar for TMC 83... circuit breakers (three phase) 17.8 mm pitch, up to 57 positions. Rated for 80 A (end feed) 600 V AC/DC. UL 508 Listed for connection of UL 489 rated circuit breakers.

Wiring bridge

Wiring bridge - TMC 8 B3 80 48 CA - 2907997

<https://www.phoenixcontact.com/us/products/2907997>



Bus bar for TMC 83... circuit breakers (three phase) with auxilliary switch. 17.8 mm pitch, up to 48 positions. Rated for 80 A (end feed) 600 V AC/DC. UL 508 Listed for connection of UL 489 rated circuit breakers.

Thermomagnetic device circuit breaker - TMC 83C 63A



1010291

<https://www.phoenixcontact.com/us/products/1010291>

Terminal adapter

Terminal adapter - TMC 8 B TERM PIN - 2907998

<https://www.phoenixcontact.com/us/products/2907998>

Feeder terminal adapter for TMC 8..... circuit breaker bus bars. Rated for 1000 V AC/DC, 115 A. Wire range 14...2 AWG. UL Listed for connection to UL 489 rated circuit breakers.



Wiring bridge end cover

Wiring bridge end cover - TMC 8 B END CAP - 2907999

<https://www.phoenixcontact.com/us/products/2907999>

Protective end covers for TMC 8 bus bars



Thermomagnetic device circuit breaker - TMC 83C 63A




1010291

<https://www.phoenixcontact.com/us/products/1010291>

Protective cover

Protective cover - TMC 8 B BUS CAP - 2908000

<https://www.phoenixcontact.com/us/products/2908000>



Protective covers for TMC 8 bus bars. Cuttable, three positions, yellow.

Thermomagnetic device circuit breaker

Thermomagnetic device circuit breaker - TMC 7/8 AUX - 2908219

<https://www.phoenixcontact.com/us/products/2908219>



Thermomagnetic device circuit breaker, number of positions: 1, connection method: Screw, cross section: 1 mm²- 35 mm², AWG: 18 - 2, mounting type: Snaps on to side of circuit breaker, Color: gray

Thermomagnetic device circuit breaker - TMC 83C 63A



1010291

<https://www.phoenixcontact.com/us/products/1010291>

Thermomagnetic device circuit breaker

Thermomagnetic device circuit breaker - TMC 7/8 ALARM - 2908220

<https://www.phoenixcontact.com/us/products/2908220>



Thermomagnetic device circuit breaker, number of positions: 1, connection method: Screw, cross section: 1 mm²- 35 mm², AWG: 18 - 2, mounting type: Snaps on to side of circuit breaker, Color: gray

Thermomagnetic device circuit breaker

Thermomagnetic device circuit breaker - TMC 7/8 12VDC SHNT - 2908221

<https://www.phoenixcontact.com/us/products/2908221>



Thermomagnetic device circuit breaker, number of positions: 1, connection method: Screw, cross section: 1 mm²- 35 mm², AWG: 18 - 2, mounting type: Snaps on to side of circuit breaker, Color: gray

Thermomagnetic device circuit breaker - TMC 83C 63A



1010291

<https://www.phoenixcontact.com/us/products/1010291>

Thermomagnetic device circuit breaker

Thermomagnetic device circuit breaker - TMC 7/8 24VDC SHNT - 2908222

<https://www.phoenixcontact.com/us/products/2908222>



Thermomagnetic device circuit breaker, number of positions: 1, connection method: Screw, cross section: 1 mm²- 35 mm², AWG: 18 - 2, mounting type: Snaps on to side of circuit breaker, Color: gray

Thermomagnetic device circuit breaker

Thermomagnetic device circuit breaker - TMC 7/8 48VDC SHNT - 2908224

<https://www.phoenixcontact.com/us/products/2908224>



Thermomagnetic device circuit breaker, number of positions: 1, connection method: Screw, cross section: 1 mm²- 35 mm², AWG: 18 - 2, mounting type: Snaps on to side of circuit breaker, Color: gray

Thermomagnetic device circuit breaker - TMC 83C 63A



1010291

<https://www.phoenixcontact.com/us/products/1010291>

Thermomagnetic device circuit breaker

Thermomagnetic device circuit breaker - TMC 7/8 125VDC SHNT - 2908225

<https://www.phoenixcontact.com/us/products/2908225>



Thermomagnetic device circuit breaker, number of positions: 1, connection method: Screw, cross section: 1 mm²- 35 mm², AWG: 18 - 2, mounting type: Snaps on to side of circuit breaker, Color: gray

Thermomagnetic device circuit breaker

Thermomagnetic device circuit breaker - TMC 7/8 120VAC SHNT - 2908226

<https://www.phoenixcontact.com/us/products/2908226>



Thermomagnetic device circuit breaker, number of positions: 1, connection method: Screw, cross section: 1 mm²- 35 mm², AWG: 18 - 2, mounting type: Snaps on to side of circuit breaker, Color: gray

Thermomagnetic device circuit breaker - TMC 83C 63A



1010291

<https://www.phoenixcontact.com/us/products/1010291>

Thermomagnetic device circuit breaker

Thermomagnetic device circuit breaker - TMC 7/8 240VAC SHNT - 2908227

<https://www.phoenixcontact.com/us/products/2908227>



Thermomagnetic device circuit breaker, number of positions: 1, connection method: Screw, cross section: 1 mm²- 35 mm², AWG: 18 - 2, mounting type: Snaps on to side of circuit breaker, Color: gray

Thermomagnetic device circuit breaker

Thermomagnetic device circuit breaker - TMC 7/8 277VAC SHNT - 2908228

<https://www.phoenixcontact.com/us/products/2908228>



Thermomagnetic device circuit breaker, number of positions: 1, connection method: Screw, cross section: 1 mm²- 35 mm², AWG: 18 - 2, mounting type: Snaps on to side of circuit breaker, Color: gray

1010291

<https://www.phoenixcontact.com/us/products/1010291>

Label

Label - EML (10X4)R - 0815583

<https://www.phoenixcontact.com/us/products/0815583>



Label, Roll, white, unlabeled, can be labeled with: THERMOMARK E.300 (D)/600 (D), THERMOMARK ROLL 2.0, THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK ROLLMASTER 300/600, THERMOMARK X1.2, mounting type: adhesive, lettering field size: 10 x 4 mm, Number of individual labels: 10000

Marker strip

Marker strip - TML (104X3,8)R - 0801833

<https://www.phoenixcontact.com/us/products/0801833>



Marker strip, Roll, white, unlabeled, can be labeled with: THERMOMARK E.300 (D)/600 (D), THERMOMARK ROLL 2.0, THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK ROLLMASTER 300/600, THERMOMARK X1.2, mounting type: adhesive, for terminal block width: 104 mm, lettering field size: 104 x 3.8 mm, Number of individual labels: 2500

Phoenix Contact 2022 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com