


Mechanical Cam Switches  
**BSE 67-RK**  
 Order Code: BSE000E

**BALLUFF**



**Basic features**

Approval/Conformity	CE UKCA CCC WEEE
Use with series	BSW 819-494

**Electrical connection**

Connection	M3.5
Connection type	1. Switch position: Screw terminal
Contact system	Single-pin changeover

**Electrical data**

Contact arrangement	NC: C+NC NO: C+NO
Contact resistance max.	20 mOhm
Contact resistance max., note	New condition
Continuous current	1. Switch position: 6.0 A
Mechanical life expectancy min.	30 mil. switching operations
Minimum load at 24 V DC	20 mA
Nominal voltage	500 VAC
Switching actuation force max.	3.60 N
Switching capacity at 220 V DC	0.25 A, L/R = 200ms
Switching capacity at 250 V AC 40...60Hz	15 A cos $\phi$ = 0.8
Switching capacity at 480 V AC 40...60Hz	15 A cos $\phi$ = 1
Switching operations per minute	300
Switching principle	Snap switch

**Environmental conditions**

Ambient temperature	-5...80 °C
---------------------	------------

**Material**

Material contacts	Silver
Material contacts	1. Switch position: Silver

**Mechanical data**

Connection cross-section	1.5 mm <sup>2</sup>
Switching actuation force min.	2.00 N
Tightening torque max.	120 Ncm