



CABLE LENGTH	TOLERANCE *
ALL LENGTHS	+ 4% (OR 50mm) OF LENGTH - 0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER
STRIP LENGTH	TOLERANCE*
0-7mm	±0.5mm
8-29mm	±1.0mm
30-49mm	±2.0mm
50-69mm	±3.0mm
70-100mm	±4.0mm
OVER 100mm	±5.0mm
* UNLESS OTHERWISE SPECIFIED	

SOURCE DRAWING - FOR REFERENCE ONLY

3000 CAMPUS DRIVE

THIS DRAWING IS CONFIDENTIAL AND THE MINNEAPOLIS, MN 55441 PROPERTY OF TURCK INC. USE OF THIS -800-544-7769 **1** 2. (763) 553-7300 DOCUMENT WITHOUT WRITTEN PERMISSION IS 3. (763) 553-0708 fax NOTES: www.turck.us MATERIAL DESCRIPTION DATE 07/27/07 RDS 1. "*" DESIGNATES CABLE LENGTH IN METERS. CONTACT TURCK TO ORDER VBRS 4.4-2PKG 3M-*/*/CS11611 ALL DIMENSIONS DISPLAYED ON THIS DRAWING ARE FOR SCALE 1=1.0 APVD SPECIFIC LENGTHS. SEE SPECIFICATIONS (a) (b) UNIT OF MEASUREMENT REFERENCE ONLY IDENTIFICATION NO. 2. "/CS1161" DESIGNATES CUSTOM WIRED SPLITTER, PER DRAWING. REV FINISH CONTACT TURCK FOR MORE INFORMATION **MILLIMETERS** IDENTIFY BRANCHES RDS 10/31/17 62837 SEE SPECIFICATIONS REV DESCRIPTION DATE ECO NO. DO NOT SCALE THIS DRAWING FILE: 777018851 SHEET 1 OF 1

3RD ANGLE

PROJECTION

RELATED DOCUMENTS