


SPECIFICATIONS						
CONTACT CARRIER MATERIAL	NYLON OR TPU					
MOLDED HEAD MATERIAL/COLOR	TPU/YELLOW					
CONTACT MATERIAL/PLATING	BRASS/GOLD					
COUPLING NUT MATERIAL/COLOR	NYLON/BLACK					
RATED CURRENT [A]	4.0 A					
RATED VOLTAGE [V]	250 V					
OUTER CABLE JACKET MATERIAL/COLOR	PVC/GRAY					
CONDUCTOR INSULATION MATERIAL	PVC					
NUMBER OF CONDUCTORS [AWG]	4x22 AWG					
DRAIN/SHIELD	24 AWG DRAIN/ALUMI./POLYESTER FOIL SHIELD					
TEMPERATURE RANGE	-40°C to +105°C (-40°F to +221°F)					
PROTECTION CLASS	NEMA 1,3,4,6P AND IEC IP68, IP69K					

SOURCE DRAWING - FOR REFERENCE ONLY

3000 CAMPUS DRIVE



RELATED DOCUMENTS

CABLE LENGTH	TOLERANCE					
ALL LENGTHS	+ 4% (OR 50mm) OF LENGTH - 0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER					
STRIP LENGTH	TOLERANCE					
0-7mm	±0.5mm					
8-29mm	±1.0mm					
30-49mm	±2.0mm					
50-69mm	±3.0mm					
70-100mm	±4.0mm					
OVER 100mm	±5.0mm					

REV DESCRIPTION

G UPDATE CABLE DIAMETER

- 1. "\*" INDICATES CABLE LENGTH IN METERS. CONTACT TURCK TO ORDER SPECIFIC LENGTHS.
- 2. "/S618" DESIGNATES CABLE WITH FOIL SHIELD AND DRAIN. DRAIN IS NOT CONNECTED AT THE CONNECTOR.

ORDER			1. 2. 3. 4.		CONFIDENTIAL AND THE PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED.		TURCK INC High Technology Sensors and Automation Controls			MINNEAPOLIS, MN 55441 1-800-544-7769 (763) 553-7300 (763) 553-0708 fax turck.com	
À.	IN IS NOT		MATERIAL SEE SPECIFICATIONS	ALL DIMENSIONS DISPLAYED ON THIS	DRFT	RWC	DATE 06/04/07 SCALE 1=1.0	DESCRIPTION	RKK 4.4T-	-*/S618	
Y 01/20/12 37153			FINISH	DRAWING ARE FOR REFERENCE ONLY CONTACT TURCK FOR MORE INFORMATION	UNIT OF MEASUREMENT		IDENTIFICATION	NO.		REV	
		37153	SEE SPECIFICATIONS		MILLIMETER [ INCH ]						G
	DATE	ECO NO.	SEE SI EGII IGATIONS	IN CINIM CICIA	DO NOT SCALE THIS DRAWING			FILE: 777003	3484	SHE	ET 1 OF 1

THIS DRAWING IS

3RD ANGLE

## NOTES: