# 

CGS | CGS 3430 TE Internal #: 2-2176555-4 110K Ω, Thick Film, Power Resistor, 1 %, 2 Termination, 0508, Taped & Reeled, 1 W, ±100 ppm/°C, Solder, 1.25 x 2 x .55 mm, CGS 3430 View on TE.com >



Passive Components > Resistors > Surface Mount Resistors



Resistor Type: Power Resistor

Number of Terminations: 2

Package Size Code: 0508

Packaging Method: Taped & Reeled

Passive Component Tolerance: 1%

## Features

## Product Type Features

Product Type	Fixed Resistor
Resistor Type	Power Resistor
Package Size Code	0508
Element Type	Thick Film
Configuration Features	
Number of Resistors	1
Electrical Characteristics	
Voltage Rating	200 V
Passive Component Tolerance	1 %
Resistance Class	$1k\Omega - 1M\Omega$
Resistance Value	110ΚΩ
Resistance Value Power Rating	110K Ω 1 W

## 3430A2F110KTDF

110K Ω, Thick Film, Power Resistor, 1 %, 2 Termination, 0508, Taped & Reeled, 1 W, ±100 ppm/°C, Solder, 1.25 x 2 x .55 mm, CGS 3430



Surface Mount Resistor Termination Type	Solder
Dimensions	
Passive Component Dimensions	1.25 x 2 x .55 mm
Usage Conditions	
Operating Temperature Range	-55 – 155 °C
Temperature Coefficient	±100 ppm/°C
Packaging Features	
Packaging Method	Taped & Reeled
Packaging Method Product Compliance For compliance documentation, visit the product page on TE.com> EU RoHS Directive 2011/65/EU	
Product Compliance For compliance documentation, visit the product page on TE.com>	Taped & Reeled Compliant with Exemptions Compliant with Exemptions
Product Compliance For compliance documentation, visit the product page on TE.com> EU RoHS Directive 2011/65/EU	Compliant with Exemptions

### Halogen Content

Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free

Reflow solder capable to 260°C

### Solder Process Capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# **Compatible Parts**

## 3430A2F110KTDF

110K Ω, Thick Film, Power Resistor, 1 %, 2 Termination, 0508, Taped & Reeled, 1 W, ±100 ppm/°C, Solder, 1.25 x 2 x .55 mm, CGS 3430





# Also in the Series | CGS 3430



## Documents

Product Drawings 3430 A2 1% 110K 100ppm 1k RL English

## **CAD** Files

**Customer View Model** 

ENG\_CVM\_CVM\_2-2176555-4\_BA.3d\_igs.zip

English

Customer View Model

ENG\_CVM\_CVM\_2-2176555-4\_BA.3d\_stp.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_2-2176555-4\_BA.2d\_dxf.zip

English

3D PDF

3D

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

Datasheet - CGS 3430 Series

English

Automotive Grade Wide Terminal Chip Resistor - Type 3430 Series

English